

- > service machine for the cot maintenance workshop
- > for long cots and short cots
- > made in Germany
- > with Neuenhauser Automation
- > universal



Semi automatic Cot Grinding SZ2 HA



Application

Rosink's new machine SZ2 HA serves for semi-automatic grinding of all centre guided top rollers, OE, texturizing and long cots, like draw frame and comber. All Rosink machines are equipped with premium components. Convenient operation through touch screen display with integrated famous Rosink grinding and polishing functions.

Advantages

- > Semi-automatic grinding of all cots, short and long!
- > Universal quick grippers to hold all kind of top rollers
- > High production output
- > Improved dust exhaust system with cooling function
- > Extension to fully automatic grinding possible by adding the new Module Automatic, SZ2A

SZ2 HA	
Dimensions HxWxD	1305 mm x 1300 mm x 725 mm
Net weight	490 kg
Power	5,2 kW
Stone	
Grain	120
rpm	2400
Traversing	16 mm
Width/Diameter	410 mm Ø 250 mm
Average Lifetime	up to 8 years
Work programmes	
Automatic	yes
Grinding to size	yes
Differential grinding	yes
Grinding accuracy	RA freely adjustable Cylindricity 0,02 / Roundness 0,00
Area of application	All cots
Working Range	
Min. diameter	20 mm
Max. diameter	80 mm
Max. axle length	520 mm
Features	
Dust extractor	yes
Standard tools	included
Safety	CE standard

SZ2 A	
Power	5,23 KW
Dimensions SZ2 HA	1305 mm x 1300 mm x 725 mm
Dimensions A-Modul	960 mm x 750 mm x 1950 mm
Net Weight	SZ2 HA 490 kg A -Modul 550kg



UV Treatment Machine